

Ceiling rose cover

Surface mounted ceiling rose with a lighting plug socket, earthed, bipolar, class 1, IP20

Type: AKK13


GTIN: 6410011525128



Ceiling rose AKK13 is an earthed, bipolar class 1 ceiling rose. AKK13 crown cover can be mounted directly onto the ceiling or, in surface mounting, onto the junction box. The group cables, 2,5 mm² (-o-), may be continued. Each ceiling rose can carry a max. 6 A 250 V lighting appliance up to the weight of 15 kilos. The hook in the ceiling rose is released when the cover is opened. Smallest compatible conductor size 1.5 mm².

Technical specification

e)



General Information

Product ID:	2TKA001667G1	
Classification		
Enclosure class:	IP20	
Packing		
Package:	5/50	
. achager		

ETIM Data

Customer service puh. +358 10 222 1999 contact.center@fi.abb.com

Product Card Surface mounted ceiling rose with a lighting plug socket, earthed, bipolar, class 1, IP20



With signal lamp:	No
Number of units:	1
Number of socket outlets switchable:	1
Number of phases:	1
Imprint/indication:	None
With hinged lid:	No
With enhanced contact protection:	No
Label space/information surface:	No
Colour:	White
RAL-number (similar):	9010
Metallic colour:	No
Transparent:	No
Lockable:	No
Eject-mechanism:	No
Insulated mounting:	No
With function lighting:	No
With orientation lighting:	No
Over voltage protection:	No
Fault current protection:	No
With miniature fuse:	No
Special power supply:	No special power supply
Mounting method:	Surface mounted (plaster)
Type of fastening:	Mounting with screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Yes
Surface protection:	Untreated
Surface finishing:	Matt
Anti-bacterial treatment:	No
With loop through function:	No
With on/off switch:	No
Rotated central insert:	No
Nominal current:	6 A

_

Customer service puh. +358 10 222 1999

contact.center@fi.abb.com

ABB Exchange +358 10 22 11

_

Product Card Surface mounted ceiling rose with a lighting plug socket, earthed, bipolar, class 1, IP20



Nominal voltage:	250 V
Frequency:	5060 Hz
Suitable for degree of protection (IP):	IP20
Impact strength:	ΙΚΟΟ
Device width:	115 mm
Device height:	30 mm
Device depth:	115 mm

_

Customer service

puh. +358 10 222 1999 contact.center@fi.abb.com